

KRUD KUTTER® PRO LOW FOAM FLOOR CLEANER

DESCRIPTION AND USES

Krud Kutter® Pro Heavy Duty Low Foam Floor Cleaner is a professional strength formula designed to clean industrial floors found in manufacturing facilities, waste management facilities, transportation maintenance facilities, warehouses and other industrial settings. The low foam formula is ideal for removing tough dirt, salt, grease and grime commonly found on industrial floors. This highly effective detergent cleans and brightens floors, leaving behind a subtle, crisp lemon scent.

Product can be used manually or with an auto-scrubber machine. Safe and effective on a variety of surfaces including concrete, ceramic tile, quarry tile, stainless steel and steel.

PRODUCT		
DESCRIPTION (128 Oz.)	SKU	
Low Foam Floor Cleaner	382263	

PRODUCT APPLICATION

DIRECTIONS

(Read entire directions and warnings prior to use.)

For best results sweep and vacuum area to be cleaned. When applying with an auto-scrubber, add appropriate amount of product based on desired dilution. When applying manually, dilute as needed, apply thoroughly with mop, rinse with clean mop and squeegee floor dry.

NOTE: Always test in an inconspicuous area before use.

DILUTION RATIOS

Lightly Soiled Floors: 1:128 (1 oz. of Cleaner to 1 gallon of water)

Heavily Soiled Floors: 1:64 (1 oz. of Cleaner to 64 oz. of water or 2 oz. of Cleaner to 1 gallon of water)

PREVENTION

Wash hands thoroughly after handling.

PHYSICAL PROPERTIES	
	LOW FOAM FLOOR CLEANER
Clarity	Yellow
Odor	Lemon scent
рН	11.25-11.50
voc	0% by weight
Shelf Life	2 Years
Safety Information	For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Phone: 800-466-7126 www.rustoleum.com

Form: ARJ-2530 Rev.: 083123