

tough & easy  
**watco**<sup>®</sup>  
watcofloors.com



## ASPHALT PAINT

Seal, protect and beautify asphalt

### DESCRIPTION AND USES

A solvent free paint for internal and external asphalt surfaces, even in main traffic areas. Asphalt Paint is the ideal way to seal, protect and color asphalt and similar surfaces. The thick, flexible coating is easy to apply by brush or roller and is available in a range of attractive colors. Asphalt Paint is ideal for use in warehouses, plant rooms, asphalt walkways on roofs, parking lots, line markings, tennis courts, playgrounds etc.

### PACKAGING

One gallon

### APPEARANCE

Colored, low to mid sheen finish depending upon substrate and number of coats applied.

### PRODUCTS

B230429 - Navy Gray  
8230828 - Tile Red  
B230230 - Black  
8231431 - Yellow  
B2309155 - Blue

### COMPANION PRODUCTS

J510001 - 18" Roller Frame and Handle  
J510002 - 18" Replacement Roller  
J510004 - 4" Brush

tough & easy  
**watco**<sup>®</sup>  
 watcofloors.com

#### SURFACE PREPARATION

Ensure the surface is clean, sound and dry (slightly damp is acceptable), using a solvent free degreaser which can be used on asphalt and similar surfaces. Asphalt Paint can be applied to existing paint providing all poorly bonded material is removed and glossy surfaces are dulled by scuff-sanding with abrasive paper.

#### APPLICATION

Use a good quality lint free 3/8" nap roller with a phenolic core. Both 9" and 18" roller covers and frames are available. One coat is generally sufficient although a second coat may be required on very porous or very rough surfaces. Avoid applying too thickly. Do not apply externally if rain or frost is forecasted or if the temperature is below 50°F. In extreme temperature conditions, please contact a Watco Industrial Flooring Expert at (855) 627-6350.

#### CURING TIME

The product will cure in 24 hours for light traffic; allow 48 hours before bringing the area back into full service. Cold, damp or humid weather will delay curing.

#### COVERAGE

One gallon will typically cover 160-240 sq ft with one coat.

#### CLEAN UP

Clean application tools in warm soapy water before the product has started to cure.

#### PHYSICAL PROPERTIES

<b>VOLATILE ORGANIC COMPOUNDS</b>	<50 g/l
<b>PRACTICAL COVERAGE</b>	160-240 sq.ft. per gallon
<b>CURING TIME</b>	24 hrs. at 60-70°F
<b>STORAGE</b>	Store in cool, dry conditions away from direct sunlight Protect from freezing.
<b>SHELF LIFE</b>	2 years
<b>FLASHPOINT</b>	>200°F (94°C)

**WARNING:** FOR INDUSTRIAL AND COMMERCIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN. REFER TO SAFETY DATA SHEET (SDS) AND LABEL FOR ADDITIONAL SAFETY INFORMATION.

tough & easy  
**watco**<sup>®</sup>  
 watcofloors.com

Watco Industrial Flooring, Inc.  
 11 Hawthorn Pkwy., Vernon Hills, IL 60061  
 (855) 627-6350 • Fax: (855) 627-6351

©2016 Watco Industrial Flooring