



## Asphalt Repair Patch

Pothole repair for asphalt and concrete

### DESCRIPTION AND USES

A high quality, durable asphalt repair patch, suitable for use on both concrete and asphalt pavements. Repairs can be open to traffic immediately after it has been used and can be applied regardless of the weather outside. Asphalt Repair Patch is recommended for all types of pavement repair jobs such as spot repairs to driveways, parking lots, paths and more.

### PRODUCTS

A130220 - Asphalt Repair Patch

### COMPANION PRODUCTS

J510016 - 8" x 8" Tamper

### PACKAGING

60 lb. bucket

### APPEARANCE

Black asphalt

# watco®

strong and reliable

## SURFACE PREPARATION

Simply sweep out the area to be repaired with a bristled brush or broom. It is a good idea to remove any loose debris, dirt, ice, or standing water from the area to be repaired. This action will promote good adhesion and bonding.

## APPLICATION

No heating or mixing is required. Simply shovel into the pothole, crack, or rut, straight from the container. If the fault is especially deep, over six inches, apply in two inch layers, compacting each layer in succession. Shovel enough material into the fault to slightly crown the "patch". When completed compress the "patch" with a tamper. Area can be opened to traffic immediately.

## CURING TIME

Immediate, following compacting of material.

## COVERAGE

Depth and width of pothole, crack, utility cut etc. will greatly influence the coverage rate achieved. As a rule however, sixty pounds of Asphalt Repair Patch will fill 6 sq.ft. at 2" deep

## CLEAN UP

All tools should be cleaned immediately after use with mineral spirits.

## STORAGE

Always keep container tightly closed when not in use to prevent "hardening" over long periods of storage.

## PHYSICAL PROPERTIES

<b>VOLATILE ORGANIC COMPOUNDS</b>	<0 g/l
<b>PRACTICAL COVERAGE</b>	6 sq. ft. at 2" deep
<b>CURING TIME</b>	Immediately
<b>STORAGE</b>	Always keep container tightly closed when not in use to prevent "hardening" over long periods of storage
<b>SHELF LIFE</b>	2 years
<b>WARNING</b>	<b>FOR INDUSTRIAL AND COMMERCIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN. REFER TO SAFETY DATA SHEET (SDS) AND LABEL FOR ADDITIONAL SAFETY INFORMATION.</b>