



Concrete Resurfacer

Bring new life to tired and dull concrete

DESCRIPTION AND USES

Watco Concrete Resurfacer is a one coat product that seals and resurfaces damaged and worn concrete. It forms a flexible, sealed, waterproof surface that transforms old concrete surfaces.

PRODUCTS

B1050299 - Black	(WT1210003K1W)	
B1050396 - Dark Gray	(WT1210105K1W)	
B10540163 - Mid Gray	(WT1220353K1W)	

COMPANION PRODUCTS

J510040 - 18" Flat Squeegee
J510017 - Spiked Roller

PACKAGING

55 Pound Pack

APPEARANCE

Matte, slip resistant surface

watco®

strong and reliable

SURFACE PREPARATION

Ensure surfaces are clean and free of loose material by brushing with a stiff broom and clean water. Allow to become dry, or almost dry, before applying the Concrete Resurfacer. If the surface has been previously painted, remove as much paint as possible by mechanical means. Any remaining paint should be well bonded and lightly abraded to provide a key. Watco Bio-D, a bio-degradable water based degreasant, can be used for removing grease and oil. Watco Concrete Resurfacer can be applied to a damp, but not wet, surface. Damp down porous surfaces (but do not leave standing water) before application.

MIXING

Stir the contents well with a wide bladed mixing tool to ensure that the product has not settled in transit.

APPLICATION

Apply only in dry conditions (above 50°F and below 95°F). Do not apply in cold, damp conditions or when rain is forecast. In warmer conditions 75°F-95°F dry, hot surfaces should be slightly dampened first. Pour onto the surface and spread in one direction using a squeegee to achieve a smooth finish. Alternatively it can be finished with a textured roller to create an anti-slip finish. Do not apply the product in layers thicker than 2 mm. If more than one layer is required to cover a rough area or substrate, allow 24 hours between layers. Never add water to the product.

CURING TIME

Protect from rain for 6 to 12 hours following application. Touch dry/Light traffic: 24 hours at 50 - 60°F, 15 - 20 hours at 60 - 85°F. Heavy traffic: 2 - 3 days at 50 - 60°F, 2 days at 60 - 85°F.

COVERAGE

55lbs will cover approximately 86ft² at 5/64 inches thick or 160ft² at 3/64 inches thick. Coverage can depend upon texture of substrate.

CLEAN UP

Wash in water before the product dries; otherwise soak for 24 hours in white spirit.

PHYSICAL PROPERTIES

VOLATILE ORGANIC COMPOUNDS	<10 g/l
PRACTICAL COVERAGE	55lbs will cover approximately 86 sq.ft. at 5/64 inches thick or 160 sq.ft. at 3/64 inches thick
CURING TIME	Protect from rain for 6 to 12 hours following application. Touch dry/Light traffic: 24 hours at 50 - 60°F, 15 - 20 hours at 60 - 85°F. Heavy traffic: 2 - 3 days at 50 - 60°F, 2 days at 60 - 85°F
STORAGE	41° F to 77°F out of direct sunlight.
SHELF LIFE	9 months in manufacturer's unopened container
WARNING	FOR INDUSTRIAL AND COMMERCIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN. REFER TO SAFETY DATA SHEET (SDS) AND LABEL FOR ADDITIONAL SAFETY INFORMATION.