



KRUD KUTTER® PRO

CALCIUM, LIME & RUST REMOVER

DESCRIPTION AND USES

Krud Kutter® PRO Calcium, Lime & Rust Remover quickly breaks up heavy mineral deposits & rust stains. Safe, fast & effective on interior and exterior surfaces including showers & tubs, sinks, toilets, brick, glass, stucco, porcelain, plastic, stone, fiberglass, cement, masonry, vinyl, aluminum & more.

PRODUCT

SKU	DESCRIPTION
352250	28 oz. Bottle

PRODUCT APPLICATION

DIRECTIONS

Always test on an inconspicuous area first. Do not allow product to dry on the surface. Eye protection and safety gloves are recommended when using this product. Ensure adequate ventilation.

SHOWERS, SINKS & TUBS – Pour product onto a dry cloth or non-abrasive sponge and apply to the stain. Rinse immediately with cold water. Repeat if necessary.

PRODUCT APPLICATION (cont.)

DIRECTIONS (cont.)

TOILET BOWLS – Flush toilet to remove water and add 6 ounces of product. Scrub with a bristled brush until clean and flush toilet. Repeat if necessary.

EXTERIOR SURFACES – For heavy stains apply product full strength. For medium-light stains, mix equal parts of product with water (50/50). Apply directly onto the surface and allow it to sit briefly. Rub lightly with a sponge or brush until the stains are gone. Rinse with water. Heavy stains may require an additional application.

DECKS – Apply product with a scrub brush or mop. Saturate the surface and let it sit until the wood achieves the desired lightness. Rinse the surface thoroughly with water and allow it to dry.

WARNING! AVOID CONTACT WITH SKIN, EYES AND CLOTHING. Eye protection should be worn and contact lenses removed while using this product. In case of contact with eyes or skin, flush with water for at least 15 minutes. If wearing contact lenses, remove and rinse eyes. If swallowed, take large amounts of water. Do not induce vomiting. Get medical attention.

KEEP OUT OF REACH OF CHILDREN.

PHYSICAL PROPERTIES

CALCIUM, LIME & RUST REMOVER	
Composition	Water, Surfactants, Mineral salts of Organic Amide
Solvents	Water
Color	Light Yellow
pH	<1.0
VOC	0% By Weight
Odor	Mild
Practical Coverage	Varies with application type and porosity of surface
Shelf Life	3 years
Flash Point	200°F (93°C)
Safety Information	For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.