

OIL & GREASE RESISTANT SAFETY MATTING



AREAS OF USE

- Manufacturing Environments
- Oil & Lube Centers
- Auto Repair Garages



DESCRIPTION

Wide-grid walkway matting specifically designed for greasy or grimy environments. With its two-layer construction, extra-wide grid and excellent drainage, Oil & Grease Resistant Safety Matting is the perfect defense against grease, grime and oil. Made from non-porous PVC with a two-layer construction, Oil & Grease Resistant Safety Matting is impermeable to fluids and provides excellent drainage, making it ideal for environments where spillages are likely. Its diamond cut pattern provides the highest slip resistance, and the wide grid means it's perfect for environments where oils and greasy materials are present, like railway maintenance areas, construction sites and processing plants.

FEATURES




Diamond Cut Pattern Surface



Two-layer construction with extra wide grid



Made from non-porous plasticised PVC



Comes in 33' rolls



Made from flexible PVC

BENEFITS



Certified Slip Resistant
(ASTM 1677: 0.9/0/7)



Excellent Drainage



Resistant to chemicals, acids, oils



Quick to Install



Easy to clean with a high pressure hose

Standard Sizes:

Product	Oil & Grease Resistant Safety Matting
Height	5/8" (15mm)
Standard roll options	33' x 2' (10 x 0.6m)
	33' x 3' (10 x 0.91m)
	33' x 4' (10 x 1.22m)
Weight	0.94lb/sq.ft (4.6kg/m ²)

Tolerances:

	Height (+/- 0.05")	Length (0+1.0')	Width (+/- 1cm)
Oil & Grease Resistant Safety Matting	5/8"	33'	2' 3' 4'

All dimensions are nominal

Technical information:

Acoustic	Excellent sound absorption
Chemical	Resistant to most acids, alkalines and oils.
Composition	Flexible Polyvinyl Chloride (PVC)
Environment	When manufactured in black, it's made using our post industrial recycled material. The recycled content averages at least 30%, but we strive for 100% wherever possible. We don't use any substances included in the SVHC list under REACH in any of our matting products.
Hygiene	Made from non-porous PVC that's naturally resistant to bacteria growth.
Reversion	Thermoplastic shrinkage can result in size reductions up to 2%. This may be accelerated in hot environments.
Slip resistance	ASTM F 1677 - Dry/Wet: 0.9/0.7 DIN 51130: R11, V10
Thermal	Designed to function at temperatures from -9°F and up to +140°F. Slight size variation may occur at temperature extremes.
UV light	Resistant to PVC degradation
Warranty	Three years.

Installation:

Oil & Grease Resistant Safety Matting's one-piece construction means installation is simple:

- Comes in 33' rolls
- Easy to cut to fit on site
- Contours to uneven surfaces

Cleaning:

Keeping Oil & Grease Resistant Safety Matting looking good is easy:

- Light to handle
- Simply roll or lift to clean
- No special cleaning tools needed

Colors:



Black