

RUST-OLEUM® PROFESSIONAL CLEANERS FOAMING CLEANER AND DEGREASER AEROSOL

DESCRIPTION AND USES

Rust-Oleum® Professional Cleaner Degreaser's aerosol foaming action clings to surfaces to quickly remove a variety of tough soils, including grease, oil, paint, adhesive, tar and wax, from most non-porous surfaces without leaving a residue. Ideal for industrial cleaning applications and for use on tools, machinery, engine parts, construction equipment, fiberglass, unfinished concrete, masonry, asphalt and more. This fast-acting degreaser is color fast and fabric safe. Foaming Cleaner Degreaser may also be used for HVAC coil cleaning.

PRODUCTS

 SKU
 DESCRIPTION

 352239
 20 oz. Aerosol

PRODUCT FEATURES

- Does Not Leave a Residue
- Fast Acting
- · Removes the Toughest Oil, Grease, Tar & Grime
- For Use on Machinery, Engine Parts, Tools & More
- · Safe for Use on Most Non-Porous Surfaces
- · Works on Unfinished Concrete

PRODUCT APPLICATION

READ ALL DIRECTIONS CAREFULLY BEFORE STARTING PROJECT

NOTE DO NOT STRIKE CAN. Always spot test on a hidden area first.

DIRECTIONS

- 1. Shake can.
- Remove cap and be sure spray nozzle is pointed toward surface to be cleaned.
- 3. Hold can about 8 inches from surface and spray on a light coating.
- 4. Allow 1 minute for foam to penetrate then use a wet cloth to clean the surface.

NOTE For heavy soils allow foam to penetrate for 2 to 5 minutes, scrub with a brush or scouring pad and wash off with a wet cloth. When used in a food processing facility, rinse with potable water after use.

HVAC COIL CLEANING

Rust-Oleum Professional Cleaner Degreaser's blend of special surfactants and alkaline cleaners make it effective for removing dust, grease, oil, and other dirt on most HVAC coils, especially condenser and evaporator coils. Turn off power to unit prior to cleaning. When using the Rust-Oleum Professional Cleaner Degreaser aerosol foam, spray directly on coils to be cleaned. Avoid spraying Cleaner Degreaser on to electrical wires. Rust-Oleum Professional Cleaner Degreaser is self-rinsing on condensate producing coils; otherwise rinse clean with water or wipe clean with a damp cloth. Return power to unit once the process is complete.

PREVENTION

Contents under pressure. Do not pierce, strike or burn, even after use. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.



Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, Illinois 60061

Phone: 800-466-7126 www.rustoleum.com Form: RAK-72 Rev.: 032225



RUST-OLEUM® PROFESSIONAL CLEANERS FOAMING CLEANER AND DEGREASER AEROSOL

PHYSICAL PROPERTIES	
	FOAMING CLEANER AND DEGREASER
Composition	Water, Isopropyl Alcohol, Detergents, Fragrance and Dye
Color	Slight Yellow
Clarity	Clear
pH	6.0-8.5
VOC	9.29% By Weight
Practical Coverage	Varies with application type
Shelf Life	5 years
Flash Point	-155°F (-104°C)
Safety Information	For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation
11 Hawthorn Parkway Phone: 800-466-7126
Vernon Hills, Illinois 60061 www.rustoleum.com

Form: RAK-72 Rev.: 032225