



RUST-OLEUM® PROFESSIONAL CLEANERS CONCENTRATED CLEANER DEGREASER

DESCRIPTION AND USES

Rust-Oleum Professional Cleaner Degreaser quickly removes a variety of tough soils, including grease, oil, paint, adhesive, tar and wax, from most non-porous surfaces without leaving a residue. Ideal for industrial cleaning applications and for use on tools, machinery, engine parts, construction equipment, fiberglass, unfinished concrete, masonry, asphalt and more. This fast-acting degreaser is color fast and fabric safe.

PRODUCTS

SKU	DESCRIPTION
352263	32 oz. Trigger Sprayer
352261	1 gal. Bottle
352257	5 gal Pail
352255	55 gal Drum
352254	275 gal Tote

PRODUCT FEATURES

- Fast-Acting Industrial Strength Degreaser
- Removes The Toughest Oil, Grease, Grime And Tar
- Does Not Leave A Residue
- For Use On Machinery, Engine parts, Tools and More
- Safe For Use On Most Non-Porous Surfaces
- Works On Unfinished Concrete

PRODUCT APPLICATION

READ ALL DIRECTIONS CAREFULLY BEFORE STARTING PROJECT

APPLICATION

NOTE Spot test on a hidden area first.

1. Apply directly to surface to be cleaned.
2. Allow product to penetrate briefly.
3. Wipe off with a clean cloth or towel.

For more difficult jobs apply a generous amount of cleaner and allow to stand for a few minutes before wiping.

For extremely tough jobs, such as the removal of old, dried latex paint, scrub with a brush or scouring pad and wash off with a wet rag.

Do not use on varnished surfaces or leather. When used in a food processing facility, rinse with potable water after use.

Do not mix this product with any other chemicals.

WARNING! KEEP OUT OF REACH OF CHILDREN.

PRODUCT APPLICATION (cont.)

PRESSURE WASHER APPLICATION

Contains anti-corrosive agents to safeguard pressure washer parts (bleach can erode O-rings). Please be aware that water pressure alone may remove paint or highlight existing discoloration caused by sun exposure.


Rinse surrounding plants with water before and after application. Wet the surface to be cleaned prior to applying the product. Place detergent application siphon tube and screen filter directly into container. Open the meter valve (if applicable) for maximum product flow. For reservoir machines, pour product (full strength) into pressure washer. Spray at low pressure onto a wet surface. On vertical surfaces, always spray from the top down. Allow product to remain on the surface for 3 to 5 minutes to penetrate. Do not allow product to dry on surface. Remove siphon tube from solution and rinse surface with high-pressure spray thoroughly. Flush siphon tube with clean water prior to storage.

HVAC COIL CLEANING

Rust-Oleum Professional Cleaner Degreaser's blend of special surfactants and alkaline cleaners make it effective for removing dust, grease, oil, and other dirt on most HVAC coils, especially condenser and evaporator coils. Turn off power to unit prior to cleaning. When using the Rust-Oleum Professional Cleaner Degreaser aerosol foam, spray directly on coils to be cleaned. Concentrate formulas should be diluted at a 1:3 ratio (1 part Rust-Oleum Professional Cleaner Degreaser to 3 parts water), and the use of a trigger sprayer, pump sprayer or other pressurized applicator is recommended to ensure proper foaming action. Avoid spraying Cleaner Degreaser on to electrical wires. Rust-Oleum Professional Cleaner Degreaser is self-rinsing on condensate producing coils; otherwise rinse clean with water or wipe clean with a damp cloth. Return power to unit once the process is complete.

CARPET CLEANING AND STAIN REMOVAL

Rust-Oleum Professional Cleaners Cleaner Degreaser is safe for all carpet types, including synthetic as well as stain resistant carpets. Test in an inconspicuous area first. The concentrated formula will clean six 9' x 12' (2.5m x 4.0m) carpets. Coverage may vary depending on type and condition of carpet. Vacuum the carpet thoroughly. Pre-treat any stubborn spots or stains by using the undiluted concentrate as a stain remover prior to cleaning carpet. Add concentrate to the receiving/waste tank of the machine to reduce buildup. Add 4 oz. of concentrate for each gallon of water in the dispensing/fill tank. For heavy traffic areas or heavily soiled carpets, add 6 oz. of concentrate for each gallon of water. Use hot (not boiling) or cold water according to the carpet manufacturer's cleaning directions. Read machine instructions carefully. Do not overfill.

	TECHNICAL DATA	ROPC-002
	RUST-OLEUM® PROFESSIONAL CLEANERS CONCENTRATED CLEANER DEGREASER	

PHYSICAL PROPERTIES

	CONCENTRATED CLEANER DEGREASER
Composition	Proprietary Blend of Biodegradable Surfactants, Detergents and Emulsifiers
pH	12.5-13.5
Color	Colorless
Odor	Mild
Volatile Organic Compounds	Non-Aerosol 0% By Weight Aerosol 5% By Weight
Practical Coverage	Heavy Soils (Full Strength) – 200-300 sq.ft./gal. Medium Soils (10 to 1) – 2,200-3,300 sq.ft./gal. Light Soils (30 to 1) – 6,200-9,300 sq.ft./gal.
Shelf Life	Non-Aerosol 7 years Aerosol 5 years
Flash Point	Non-Aerosol >200°F (>93°C) Aerosol -155°F (-104°C)
Caution!	In case of contact with eyes or skin, flush with water for at least 15 minutes. If irritation persists, seek medical attention. If swallowed, take large amounts of water. Do not induce vomiting. Get medical attention. KEEP OUT OF REACH OF CHILDREN.
Safety Information	For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061

Phone: 800-4667126
www.rustoleum.com

Form: RAK-52
Rev.: 011725